

This report is not valid if the serial number has been defaced or altered **20601520**

)

DPN18C

DOMESTIC ELECTRICAL INSTALLATION CONDITION REPORT

Small installations up to 100 A single phase supply

Issued in accordance with BS 7671: 2018 – Requirements for Electrical Installations

PART 1: DETAILS OF THE CONTRACTOR, CLIENT AND INSTAL	LATION	
DETAILS OF THE CONTRACTOR 000 Registration No: 501766000 Branch No: Trading Title: Advanced Electrical Services York Ltd Address: Office 1 York Eco Business Centr, York Amy Johnson Way, York	DETAILS OF THE CLIENT Contractor Reference Number (CRN): Name: Adam Bennett Address: Adam Benett, 58 Gillygate, YORK	DETAILS OF THE INSTALLATION Unknown Occupier: Address: 22 Bad Bargain Lane, YORK
Postcode: YO30 4AG Tel No: 01904479485	Postcode: YO31 7EQ Tel No: N/A	Postcode: YO31 0QZ Tel No: N/A
PART 2 : PURPOSE OF THE REPORT		
Purpose for which this report is required: To verify the condition of the elect	ctrical installation within the property	
Date(s) when inspection and testing was carried out: (22/10/2019) Records available: (vailable: (
PART 3 : SUMMARY OF THE CONDITION OF THE INSTALLATIO	N	
General condition of the installation (in terms of electrical safety): The installation appears to be in reasonable condition with regards to	electrical safety	
Estimated age of electrical installation: (20	f additions or alterations: (allation is: Satisfactory, XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
PART 4 : DECLARATION		
REVIEWED BY QUALIFIED SUPERVISOR Name (capitals): MATTHEW CHIPCHASE	Signature:	Date: 25/10/2019
*An unacticfactory account indicates that democracy (CODE C1) and/or notanticlly dem		ORE Ell without delaw in required

*An unsatisfactory assessment indicates that dangerous (CODE C1) and/or potentially dangerous (CODE C2) conditions have been identified in PART 6, or that Further Investigation (CODE FI) without delay is required.

 This report is based on the model forms shown in Appendix 6 of BS 7671

 Published by Certsure LLP
 Certsure LLP operates the NICEIC & ELECSA brands

 Warwick House, Houghton Hall Park, Houghton Regis, Dunstable, LU5 5ZX



This report is not valid if the serial number has been defaced or altered

20601520

DOMESTIC ELECTRICAL INSTALLATION CONDITION REPORT

Small installations up to 100 A single phase supply

Issued in accordance with BS 7671: 2018 – Requirements for Electrical Installations

PART 5 : NEXT INSPECTION													
I/We (as indicated on page 1) recommend that subject to the necessary remedial work being taken, this installation Give reason for recommendation:	-												
PART 6 : OBSERVATIONS AND RECOMMENDATIONS FOR ACTIONS TO BE TAKEN													
CODES: One of the following Codes, as appropriate, has been allocated to each of the observations made below to indicate to the person(s) responsible for the electrical installation the degree of urgency for remedial action Risk of injury. Immediate		CODE C3 'Improvement Recommended'	CODE FI 'Further Investigation Require										
Referring to the Schedule of Items Inspected (see PART 10), the attached Schedule of Circuit Details and Test Results (see There are no items adversely affecting electrical safety (), OR The following observations and recomm		PART 7 :											
Item No Observation (1) (5.11 c)No RCD protection for cables buried less 50mm deep in building fabric/plaster etc	(s))	Code (C3	Location Reference									
(2) (6.2 b)Cooker switch is located slightly behind the hob)	(C3)	()									
() (,	()	()									
() (,	()	()									
() (()	()									
() ()	()	()									
() ()	()	()									
() (,	()	()									
() (,	()	()									
() (()	()									
() (()	()									
() ()	()	()									
() ()	()	()									
() (()	()									
() (()	()									
Additional pages? (None) State page numbers: (N/A			()										
Immediate action required for items: (N/A) Improvement recommended for items: (1.2)									
Urgent remedial action required for items: (N/A) Further investigation required for items: $(\frac{N}{A})$	Α)									

*The proposed date for the next inspection should take into consideration any legislative or licensing requirements and the frequency and quality of maintenance that the installation can reasonably be expected to receive during its intended life. The period should be agreed between relevant parties.

DPN18C



This report is not valid if the serial number has been defaced or altered

20601520

DOMESTIC ELECTRICAL INSTALLATION CONDITION REPORT

Small installations up to 100 A single phase supply

Issued in accordance with BS 7671: 2018 – Requirements for Electrical Installations

DPN18C

PART 7 : DETAILS AND LIMITATIONS ON THE INSPECTION AND TESTING												
the building or underground, have not been visually inspected unless specifically ag	s amended. Cables concealed within trunking and conduits, or cables and conduits co reed between the Client and the Inspector prior to inspection. s detailed within this report											
any building voids or loft spaces	No Live to neutral insulation resistance tests carried out to prevent dama	ge to connected equipment. No inspect	ion has been carried out in									
		Agreed with (print name): CLIENT										
Extent of sampling (inspection only): 20% of accessories have been visual	ly checked for compliance.		(see additional page No. N/A)									
Operational limitations including the reasons. Unable to determine size and	type of main REC (electric supply company) fuse.		(see additional page No. <mark>N/A</mark>)									
PART 8 : SUPPLY CHARACTERISTICS AND EARTHING ARRANG	GEMENTS											
System type and earthing arrangements	Number and type of live conductors	Nature of supply parameters										
TN-C-S: (/N/A) TN-S: (/) TT: () Other (<i>state)</i> : N/A	AC 1-phase, 2-wire: ()	Nominal line voltage to Earth, U_0 :	(230 () V ⁽¹⁾ By enquiry, (50 , , measurement, or									
Supply protective device	Other (state): N/A	Nominal frequency, f:	(1.1) HZ by calculation									
Non vorifiable		Prospective fault current, I _{nf} ^{(1)*} :	() kA									

System type and eartning arrangements		i type of live conductors		Nature of supply parameters		
TN-C-S: () TN-S: (TT: () AC	1-phase, 2-wire: ()		Nominal line voltage to Earth, U_0 :	50	⁽¹⁾ By enquiry, measurement, or
Supply protective device (BS (EN) Non-verifiable Type: (N/A	Other <i>(state</i> Confirmatio); N/A n of supply polarity: as of supply (<i>as detailed on attached schedule)</i> Pa	(¥) age No:()	Nominal frequency, <i>f</i> : Prospective fault current, <i>I_{pf}</i> ^{(1)*} : External loop impedance, <i>Z_e</i> ^{(1)*} :	() HZ 1 22	by calculation
PART 9 : PARTICULARS OF INSTALLA	TION REFERRED TO IN THIS REPORT					
			1			
Means of Earthing	Main protective conductors	Main protective bonding connections	Main switch /	/ Switch-fuse / Circuit-breaker / RCI		
Distributor's facility:	Main protective conductors Earthing conductor:	Main protective bonding connections Water installation pipes: ()	Main switch / Type:	/ Switch-fuse / Circuit-breaker / RCl (BS (EN)		
•	Earthing conductor:	Water installation pipes: () Gas installation pipes: ()	-)
Distributor's facility: () Installation earth electrode: ()	Earthing conductor: (material Copper	Water installation pipes: () Gas installation pipes: () Structural steel: (N/A)	Туре:	(BS (EN) 60947-3 (Within consumer unit (2) R) (<mark>N/A</mark>) A
Distributor's facility: () Installation earth electrode: () Where an earth electrode is used insert	Earthing conductor:	Water installation pipes: () Gas installation pipes: () Structural steel: (N/A) Oil installation pipes: (N/A)	Type: Location:	(BS (EN) 60947-3 (Within consumer unit (2) R	.)) (<mark>N/A</mark>) A (230) V
Distributor's facility: () Installation earth electrode: () Where an earth electrode is used insert Type – rod(s), tape, etc: (None)	Earthing conductor: (material Copper	Water installation pipes: () Gas installation pipes: () Structural steel: (N/A)	Type: Location: No. of poles: Current rating:	(BS (EN) 60947-3 (Within consumer unit (2) R : (100) A V	.) lating / setting of device:	
Distributor's facility: () Installation earth electrode: () Where an earth electrode is used insert Type – rod(s), tape, etc: (None) Location: (N/A)	Earthing conductor: (material Coppercsa 16mm Connection / continuity verified: (Water installation pipes: () Gas installation pipes: () Structural steel: (N/A) Oil installation pipes: (.N/A) Lightning protection: (N/A)	Type: Location: No. of poles: Current rating: Where an RCD	(BS (EN) 60947-3 (Within consumer unit (2) R	.) lating / setting of device:	

*Where the installation is supplied by more than one source, the higher or highest values of prospective fault current, I of, and external earth fault loop impedance, Z_e, must be recorded.

(.....)

All fields must be completed. Enter either, as appropriate: '\screwt' if Acceptable condition; '**N/A**' if Not applicable; 'LIM' if a Limitation exists;

Measured operating time: (N/A....) ms

or Code appropriately - CODE 'C1', 'C2', 'C3' or 'FI' (codes to be recorded in PART 6, with additional comments (where appropriate) on attached numbered sheets)

Rated time delay:

Connection / continuity verified:

(N/A) ms



This report is not valid if the serial number has been defaced or altered **20601520**

DPN18C

DOMESTIC ELECTRICAL INSTALLATION CONDITION REPORT

Small installations up to 100 A single phase supply

Issued in accordance with BS 7671: 2018 – Requirements for Electrical Installations

PART 10 : SCHEDULE OF ITEMS INSPECTED

	tternal condition of intake equipment (visual inspection only)		4. Co	onsumer unit(s) / Distribution board(s)	4.15 Protection against electromagnetic effects where cables						
	inadequacies are identified with the intake equipment, it is recor	nmended		Adequacy of working space / accessibility to			enter metallic consumer unit / enclosure:	() (N/A)			
	e person ordering the report informs the appropriate authority)	(1	consumer unit / distribution board:			RCDs provided for fault protection – includes RCBOs:				
	Service cable:		1	Security of fixing:	()	4.17	RCDs provided for additional protection – includes RCBOs:	() , N/A			
	Service head:	()	4.3	Condition of enclosure(s) in terms of IP rating:	()	4.18	Confirmation of indication that SPD is functional:	()			
1.3	Earthing arrangement:	(•	4.4	Condition of enclosure(s) in terms of fire rating:	()	4.19	Adequacy of AFDD(s), where specified:	(N/A)			
1.4	Meter tails:		4.5	Enclosure not damaged / deteriorated so as to impair safety:	()	4.20	Confirmation that conductor connections, including				
	a) Cutout fuse to meter	()	4.6	Presence of linked main switch:	(•		connections to busbars, are correctly located in terminals	()			
	b) Meter to consumer unit	()	4.7	Operation of main switch(es) (functional check):	(and are tight and secure:	()			
1.5	Metering equipment:	()	4.8	Main switch capable of being secured in the OFF position:	(5. Di	tribution / final circuits				
1.6	Isolator (where present):	()	1	Operation of circuit-breakers and RCDs to prove		5.1	Identification of conductors:	()			
2. Pi	esence of adequate arrangements for other sources			disconnection (functional check):	()	5.2	Cables correctly supported throughout:	()			
			4.10	Correct identification of circuits and protective devices:	()	5.3	Condition of insulation of live parts:	()			
Z. I	Adequate arrangements where a generating set operates as a switched alternative to the public supply:	(N/A)	4.11	Presence of appropriate circuit charts, warning and other notic	ces:	5.4	Non-sheathed live conductors protected by enclosure in cond	luit,			
2.2	Adequate arrangements where generating set operates in	, ,		a) Provision of circuit charts/schedules or equivalent	()		ducting or trunking (including confirmation of the integrity of conduit and trunking systems):	(N/A)			
	parallel with the public supply:	(N/A () (N/A		forms of information	()		Adequacy of cables for current-carrying capacity with regard				
2.3	Presence of alternative / additional supply warning notices:	(IN/A)		 Warning notice of method of isolation where live parts not capable of being isolated by a single device 	, N/Α ,		to the type and nature of installation:	(•			
3. Ea	rthing and bonding arrangements			1 5 , 5	() . / .	5.6	Adequacy of protective devices; type and rated current for	· • .			
3.1	Presence and condition of distributor's earthing arrangement:	()		c) Periodic inspection and testing notice	() (/)		fault protection:	()			
	Presence and condition of earth electrode connection,			d) Presence of RCD six-monthly notice, where required	()	5.7	Presence and adequacy of circuit protective conductors:	()			
	where appropriate:	(N/A ()		e) Warning notice of non-standard (mixed) colours			Co-ordination between conductors and overload				
3.3	Confirmation of adequate earthing conductor size:	(•		of conductors present	()		protection devices:	()			
3.4	Accessibility and condition of earthing conductor at			f) All other required labelling provided	()		Wiring system(s) appropriate for the type and nature of the	()			
	Main Earthing Terminal (MET):	()	4.12	Compatibility of protective device(s), base(s) and other			installation and external influences:	()			
3.5	Confirmation of adequate main protective bonding conductor sizes	:: (/)		components; correct type and rating (no signs of			Cables adequately protected against mechanical damage and abrasion:	()			
3.6	Accessibility and condition of main protective bonding		1	unacceptable thermal damage, arcing or overheating):	()		Provision of additional protection by 30 mA RCD (see Note):	()			
	conductor connections:	()		Single-pole switching or protective devices in the line							
3.7	Accessibility and condition of other protective	,N/A ,	1	conductors only:	()		a) For all socket-outlets with a rated current not exceeding 32 A	• ()			
3.8	bonding connections: Provision of earthing and bonding labels at all	()		Protection against mechanical damage where cables enter consumer unit / distribution board:	()		b) For mobile equipment not exceeding a rating of 32 A for use outdoors	()			
0.0	appropriate locations:	()					c) For cables concealed in walls / partitions at a depth of less than 50 mm	(C3			

All fields must be completed. Enter either, as appropriate: '\screwt' if Acceptable condition;

n; **'N/A**' if Not applicable;

'**LIM**' if a Limitation exists;



This report is not valid if the serial 20601520 number has been defaced or altered

DPN18C

DOMESTIC ELECTRICAL INSTALLATION CONDITION REPORT

₁ None

Small installations up to 100 A single phase supply

Issued in accordance with BS 7671: 2018 – Requirements for Electrical Installations

PART 10 : SCHEDULE OF ITEMS INSPECTED

 d) For cables concealed in walls / partitions containing meta parts regardless of depth e) For all AC final circuits supplying luminaires Note: Older installations designed prior to BS 7671: 2008 may not have been p with RCDs for additional protection. 5.12 Provision of fire barriers, sealing arrangements and protection area of fire to arrange officients. 	() c) Clu () 6.3 For iso provided a) W ca 7. Current-u	Varning label(s) posted in situations where live parts annot be isolated by the operation of a single device using equipment (permanently connected)	(<u>N/A</u>)	8.4 Presence of supplementa required by <i>BS</i> 7671: 2018	ith <i>BS EN 61558-2-5</i> (formerly <i>BS 3535</i>): ary bonding conductors unless not & s) socket-outlets sited at least	(<u>N/A</u>) (<u>N/A</u>) (<u>N/A</u>) (<u>N/A</u>)
protection against thermal effects: 5.13 Band II cables segregated / separated from Band I cables: 5.14 Cables segregated / separated from communications cabling: 5.15 Cables segregated / separated from non-electrical services:	() 7.1 Conditi () 7.2 Equipm () 7.3 Enclos	tion of equipment in terms of IP rating: ment does not constitute a fire hazard: sure not damaged / deteriorated so as to impair safet bility for the environment and external influences:	()	location in terms of IP rat	or installation in a particular zone:	(v) (v)
 5.16 Termination of cables at enclosures (extent of sampling indicated in PART 7 of the report): a) Connections soundly made and under no undue strain b) No basic insulation of a conductor visible outside enclosure c) Connection of live conductors adequately enclosed d) Adequately connected at point of entry to enclosure 5.17 Condition of accessories including socket-outlets, switches and joint boxes is satisfactory: 6. Isolation and switching 	(ssed luminaires (downlighters): orrect type of lamps fitted nstalled to minimise build-up of heat lo signs of overheating to surrounding building fabric	() e No. (N/A) (N/A) (N/A)	List of all other special installatio	ns or locations, if any, present:	(N/A () () () () ()
 (isolation, switching off for mechanical maintenance and functional sw 6.1 In general: a) Presence and condition of appropriate devices b) Correct operation verified 6.2 For isolation and switching for mechanical maintenance only: a) Capable of being secured in the OFF position, where appropriate 	() () () () () ()	lo signs of overheating to conductors / terminations (s) containing a bath or shower ional protection by RCD not exceeding 30 mA: or low voltage circuits serving the location or low voltage circuits passing through Zone 1 and one 2 not serving the location	(.) (.) (<u>N/A</u>)	SCHEDULE OF ITEMS IN Name (capitals): MATTHEW F Signature: M	ISPECTED BY	19
PART 11 : SCHEDULES AND ADDITIONAL PAGES Schedule of Inspections Schedule of Circuit for the installation	t Details and Test Results		Special install (indicated in it	lations or locations tem 9. above)	Continuation sheets	

The pages identified are an essential part of this report (see Regulation 653.2).

None

All fields must be completed. Enter either, as appropriate: '\screwt' if Acceptable condition;

Page No(s):

6)

'N/A' if Not applicable;

.) Page No(s):

'LIM' if a Limitation exists:

or Code appropriately – CODE 'C1', 'C2', 'C3' or 'FI' (codes to be recorded in PART 6, with additional comments (where appropriate) on attached numbered sheets)

Page No(s):

Page No(s):

(4&5

Page No(s):

None



Warwick House, Houghton Hall Park, Houghton Regis, Dunstable, LU5 5ZX

This report is not valid if the serial number has been defaced or altered

20601520

DOMESTIC ELECTRICAL INSTALLATION CONDITION REPORT Small installations up to 100 A single phase supply

Issued in accordance with BS 7671: 2018 – Requirements for Electrical Installations

PA	RT 12 : SCHEDULE OF CIRCUIT	DET/	AILS A	ND T	EST RE	SULT	S	Circuit	s/equip	nent vu	Inerabl	e to dam	age whe	n testing	N/A				•••••		• • • • • • • • • • • • • •					
CO	DES for Type of wiring (A) Thermoplastic insulate sheathed cables	^{d /} (B)	Thermoplas metallic cor	tic cables i 1duit	in (C) n	nermoplasti on-metallic	ic cables in conduit	(D) ^{Thermo} metallic	plastic cable trunking	^{es in} (E) Thermopl	astic cables in Ilic trunking	^п (F) Тһ	ermoplastic / S	SWA cables	(G) Thermo	setting / SWA	cables (H) Mineral-insi	lated cables	(O) other	r - state:	N/A			
nber	Circuit description * Where this consumer unit is remote from	of wiring Codes)	Aethod 7)	ts served		cuit ctor csa	disconnection 1e (<i>BS 7671</i>)		Protective	device		RCD ^{UV}	Maximum permitted . Zs for installed protective device**		Circu	iit impedanc		· .	Insu	Insulation resistar		Polarity	red earth edance, Zs	RCD operating time		Test ittons
Circuit number	the origin of the installation, record details of the circuit supplying this consumer unit on the first line.	Type of wi (see Cod	Reference Method (<i>BS 7671</i>)	Number of points	Live	срс	Max. tirr	BS (EN)	Type	Rating	Short-circuit capacity	Operating current, I _{An}		Ring (mea (Line)	final circui sured end t		(comple one c	ircuits te at least column)	Live / Live	Live / Earth	Test voltage DC		Max. measured earth fault loop impedance, <i>Zs</i>		RCD	AFD
1	Fridge	Δ	С	2 1	(mm ²) 2.5	^(mm²)	(s) 0.4	61009	В	(A) 20	(kA) 6	(mA) N/A	(Ω) 2.19	r ₁	r _n N/A	r ₂	$(R_1 + R_2)$ 0.37	R ₂ N/A	(MΩ) LIM	(MΩ) 200	(V) 500	()	(Ω) 0.56	(ms)	()	(√) N/A
	-	A		1	2.5	1.5	0.4	61009	P	20	0	IN/A	2.19	IN/A	IN/A	IN/A	0.37	N/A		200	500	~	0.56	10.4	/	IN/A
<u> </u>	Spare Boiler	Δ	С	1	2.5	1.5	0.4	60898	В	16	6	N/A	2.73	N/A	N/A	N/A	0.24	N/A	LIM	200	500	./	0.43	N/A	N/A	N/A
, 1	Spare		0		2.0		0.1		-		°		2.70				0.21			200			0.10			, , .
	Spare																					-				
<i>.</i>	RCD						0.4	61008		63	6	30										~		36.1	~	N/A
	RCD						0.4	61008			-	30										~		36.1	V V	N/A
5	Cooker	Α	С	2	6	2.5	0.4	60898	в			N/A	1.37	N/A	N/A	N/A	0.16	N/A	LIM	50	500	V	0.35	N/A	N/A	N/A
7	Shower	A	C	1	-	2.5 2.5	0.4	60898	В		-	N/A	1.37	N/A	N/A		0.18	N/A	LIM	50	500	V	0.37	N/A	N/A	N/A
2	Sockets-Various	A	C	6	2.5	1.5	0.4	60898	R	-	-	N/A	2.19	N/A	N/A	N/A	0.51	N/A	LIM	50	500	~	0.70	N/A	N/A	N/A
, ,	Lights and smoke alarms	A	101	19	1	1.0	0.4	60898	В	6		N/A	7.28	N/A	N/A		0.87	N/A	LIM	50	500	V	1.06	N/A	N/A	N/A
10	Hob	A	C	1	6	2.5	0.4	60898	В	-	- 6	N/A	1.37	N/A	N/A	N/A	0.20	N/A	LIM	50	500	V	0.39	N/A	N/A	N/A
11	Sockets-Various	A	С	10	2.5	1.5	0.4	60898	В	20	6	N/A	2.19	N/A	N/A	N/A	1.09	N/A	LIM	50	500	V	1.28	N/A	N/A	N/A
12	Spare																									
	-																					+				
								1														+				
																1										
Lo	cation of consumer unit:								[Designa	tion:)B-1							Pros	pective f umer un	ault curr it <i>(where</i>	rent a e <i>app</i>	t licable)	t (1.2	22) kA	\ \
TE	STED BY Name (capitals):MATT	HEW	KING					Po:	sition:	lectricia	an				Signa	ture: /	L	R	Kr	\sim	<u> </u>	Da	te:	10/201	9	
TE	ST INSTRUMENTS (enter serial n	umber a	against	each in	istrumen	t used)																				
	ulti-function: 01736608	Contin N/A					Ins N/A	ulation res A	sistance	:		Earth N/A		op imped	ance:		Earth e N/A	lectrode	resistan	ce:		CD: V/A				
Publi	eport is based on the model forms shown in Ap shed by Certsure LLP Certsure	LLP ope	of <i>BS 76</i> erates th	71 ne NICE			ands	@ Copy	** yright Ce	* Where f rtsure L	igure is n LP (July	ot taken fr 2018)	om <i>BS 767</i>	71, state sou	urce: (N	I/A)				Page 6 c	of 6

DPN18C

NOTES FOR RECIPIENT THIS CONDITION REPORT IS AN IMPORTANT AND VALUABLE DOCUMENT WHICH SHOULD BE RETAINED FOR FUTURE USE

The purpose of a domestic periodic inspection is to determine, so far as is reasonably practicable, whether the electrical installation of a single dwelling (house or flat) is in a satisfactory condition for continued service. This report provides an assessment of the condition of the electrical installation identified overleaf at the time it was inspected and tested, taking into account the stated extent of the installation and the limitations of the inspection and testing.

The report identifies any damage, deterioration, defects and/or conditions found by the inspector which may give rise to danger (see PART 6), together with any items for which improvement is recommended.

If you were the person ordering this report, but not the user of the installation, you should pass this report, or a full copy of it including these notes, the schedules and additional pages (if any), immediately to the user.

This report should be retained in a safe place and shown to any person inspecting or undertaking further work on the electrical installation in the future. If you later vacate the property, this report will provide the new user with an assessment of the condition of the electrical installation at the time the periodic inspection was carried out.

Where the installation incorporates a residual current device (RCD) there should be a notice at or near the device stating that it should be tested every six months. For safety reasons it is important that this instruction is followed.

For safety reasons, the electrical installation should be re-inspected at appropriate intervals by a skilled person or persons, competent in such work. The recommended date by which the next inspection should be carried out is stated in PART 5 of this report. There should also be a notice at or near the main switchboard or consumer unit indicating when the next inspection of the installation is due. NICEIC* recommends that you engage the services of an NICEIC Approved Contractor for the inspection.

This report has been issued in accordance with the national standard for the safety of electrical installations, *BS* 7671: 2018 – *Requirements for Electrical Installations*.

Only an NICEIC Approved Contractor or Conforming Body is authorised to issue this NICEIC Domestic Electrical Installation Condition Report. You should have received the report marked 'Original' and the Approved Contractor should have retained the report marked 'Duplicate'.

This report form is intended to be issued only for the purpose of reporting on the condition of an existing electrical installation and must not be issued to certify new electrical installation work including the replacement of a consumer unit.

The report consists of at least six numbered pages. Additional numbered pages may have been provided to permit further relevant information relating to the installation to be recorded. For installations having more than one consumer unit or more circuits than can be recorded in PART 12, one or more additional *Schedules of Circuit Details and Test Results* should form part of the report. The report is invalid if any of the schedules identified in PART 10 are missing. The report has a printed serial number, which is traceable to the Contractor to which it was supplied.

PART 7 (Details and limitations) should identify fully the extent of the installation covered by this report and any limitations on the inspection and testing. The inspector should have agreed these aspects with the person ordering the report before the inspection was carried out.

Rarely, an operational limitation may have been encountered during the inspection such as inability to gain access to parts of the installation or to an item of equipment. The inspector should have noted any such limitations in PART 7. It should be noted that the greater the limitations applying to a report, the less its value from the safety aspect.

A declaration should have been given by the inspector in PART 4 of the report. The declaration must reflect the statement given in PART 3, which summarises the observations and recommendations made in PART 6. Where one or more observations have been made in PART 6, the Classification code given to each by the inspector indicates the degree of urgency with which remedial action needs to be taken to restore the installation to a safe working condition.

Where the inspector has indicated an observation as code C1 (danger present) **the safety of those using the installation is at risk**. Wherever practicable, items classified as (C1) should be made safe on discovery, and it is recommended that a skilled person(s) competent in electrical installation work undertakes the necessary remedial work immediately.

Where the inspector has indicated an observation as code C2 (potentially dangerous) **the safety of those using the installation may be at risk**, and it is recommended that a skilled person competent in electrical installation work undertakes the necessary remedial work as a matter of urgency.

Where the inspector has indicated that an item requires further investigation (FI), the investigation should be carried out without delay to determine whether danger or potential danger exists. For further guidance on the Classification codes, please see the reverse of page 2.

Where the installation can be supplied by more than one source, such as the public supply and a standby generator or microgenerator, this should be identified in PART 8 *Supply Characteristics and Earthing Arrangements*, and the *Schedules of Circuit Details and Test Results* (PART 12) compiled accordingly.

Where inadequacies in the intake equipment have been observed (Item 1 of PART 10), the person ordering the inspection should inform the distributor and/or supplier as appropriate.

Should the person ordering this report have reason to believe that it does not reasonably reflect the condition of the electrical installation reported on, that person should in the first instance raise the specific concerns in writing with the Approved Contractor. If the concerns remain unresolved, the person ordering this report may make a formal complaint to NICEIC, for which purpose a complaint form is available on request.

The complaints procedure offered by NICEIC is subject to certain terms and conditions, full details of which are available upon application. NICEIC does not investigate complaints relating to the operational performance of electrical installations (such as lighting levels), or to contractual or commercial issues (such as time or cost).

* NICEIC is operated by Certsure LLP, a partnership between the Electrical Contractors' Association and the charity, Electrical Safety First. NICEIC maintains and publishes registers of electrical contractors that it has assessed against particular scheme requirements (including the technical standard of electrical work).

For further information about electrical safety and how NICEIC can help you, visit **www.niceic.com**

GUIDANCE FOR RECIPIENTS ON THE CLASSIFICATION CODES

Only one Classification code should be given for each recorded Observation

Classification code C1 (Danger present)

Where an observation has been given a Classification code C1, the safety of those using the installation is at risk and immediate remedial action is required.

The person ordering the inspection is advised to take action without delay to remedy the observed deficiency in the installation, or to take other appropriate action (such as switching off and isolating the affected part(s) of the installation) to remove the danger. The NICEIC Approved Contractor issuing this report will be able to provide further advice.

NICEIC makes available 'Electrical Danger Notification' forms to enable inspectors to record, and then to communicate to the person ordering the report, any dangerous condition discovered.

Classification code C2 (Potentially dangerous)

Classification code C2 indicates that, whilst those using the installation may not be at immediate risk, urgent remedial action is required to remove potential danger. The NICEIC Approved Contractor issuing this report will be able to provide further advice.

It is important to note that the recommendation given at PART 5 of this report (Next Inspection) for the maximum interval until the next inspection is conditional upon all items which have been given a Classification code C1 and code C2 being remedied immediately and as a matter of urgency, respectively.

It would not be reasonable for the inspector to indicate that the installation is in a satisfactory condition if any observation in this report has been given a code C1 or code C2 classification.

Classification code C3 (Improvement recommended)

Where an observation has been given a Classification code C3, the inspection and/or testing has revealed a non-compliance with the current safety standard which, whilst not presenting immediate or potential danger, would result in a significant safety improvement if remedied. Careful consideration should be given to the safety benefits of improving these aspects of the installation. The NICEIC Approved Contractor issuing this report will be able to provide further advice.

Code FI (Further investigation required without delay)

It should usually be possible for the inspector to attribute a Classification code to each observation without indicating a need for further investigation.

However, where 'FI' has been entered against an observation the inspector considers that further investigation of that observation is likely to reveal danger or potential danger that, due to the agreed extent or limitations of the inspection and/or testing, could not be fully identified at the time.

It would not be appropriate for the inspector to indicate that the installation is in a satisfactory condition if there is reasonable doubt as to whether danger or potential danger exists. Consequently, where the inspector has indicated 'Further investigation required without delay' (FI) the overall assessment of the installation (PART 3) should be marked as 'Unsatisfactory'.

If the inspector has indicated that an observation requires further investigation without delay, the person ordering this report is advised to arrange for the NICEIC Approved Contractor issuing the report (or another skilled person or persons competent in such work) to undertake further examination of that aspect of the installation as a matter of urgency, to determine whether or not danger or potential danger exists.

Further information

Further information on the application of Classification codes, primarily aimed at inspectors but of possible interest to persons ordering condition reports, can be found in Electrical Safety First's Best Practice Guide No 4 *Electrical installation condition reporting: Classification Codes for domestic and similar electrical installations.* The guide can be viewed or downloaded free of charge from www. electricalsafetyfirst.org.uk

For further information about electrical safety and how NICEIC can help you, visit www.niceic.com